



## **SALIENT FEATURES & BENEFITS OF HY-POXY RANGE**

1. **Wide Range** – HYPOXY have complete range of Metal filled, Aluminium filled, Titanium filled & Ceramic filled liquids and putties to address wide range of Maintenance needs in the industry.
2. **Various Pack Sizes.** – HYPOXY have small, medium & large pack sizes for all our products, which gives customers the benefits of flexibility in selection of suitable pack sizes as per their requirements.
3. **Fast curing 5 minutes** Aluminium putties in various pack sizes.
4. **HYPOXY products range has closely linked fillers with high molecular weight polymer binders.** This ensures better and higher tensile shear adhesion strength over equivalent products from competition.
5. **Hy Poxy products cures faster & reaches to maximum strength in minimum time** ensures reduced down time.
6. **Hy Poxy products have lower water permeability.** This ensures better performance when they are exposed or immersed in water.
7. **When the cured compound is exposed to heat / temp. – dry or wet,** the mechanical properties such as Flexural strength, Compressive strength, Tensile shear adhesion strength and Hardness drops at elevated temp. The rate of fall is more steep in competition products than ours. This indicate better suitability / Retainability of mechanical properties at elevated temp in our products.
8. **HYPOXY range hardener packs are nitrogen sealed for safety, pilferage & long usable life.**
9. **HYPOXY products exhibits long shelf life of approx 5 years if stored well.**
10. **We ensure that HYPOXY products supplied to customers are not more than 5-6 month old from manufacturing date.** This ensure customer to enjoy complete 5 years period of “**BEST BEFORE USE**”